

GRAS 43AI

CCP Ear Simulator for
Production Testing Based on
ITU-T Rec. P57 Type 3.2 High-
leak



Connection: 0 V/CCP
Volume: Complex
Dyn range: 25 dB(A) to 150 dB
ANSI: S3.7

The GRAS 43AI ear simulator consists of the ITU-T Rec. P.57 Type 2 Ear Simulator and Type 3.2 Simplified High-leak Pinna Simulator and is designed for making ITU-T standardized tests of telephone handsets, receivers and receiver/loudspeaker-modules on the production line.

43AI consists of the ITU-T Rec. P57 Type 2 Ear Simulator and Type 3.2 Simplified High-leak Pinna Simulator for testing leak tolerant receivers

Besides the ear and pinna simulators, GRAS 43AI includes a detachable front-plate that can be machined to make well-defined testing on various receiver related items. A calibration adapter to be used with [GRAS 42AA Pistonphone](#)/[GRAS 42AP Pistonphone](#) is included.

Theoretical dynamic range lower limit with GRAS preamplifier	dB(A)	25
Theoretical dynamic range upper limit with GRAS CCP preamplifier	dB	150
Set sensitivity @ 250 Hz (± 2 dB)	mV/Pa	12
Set sensitivity @ 250 Hz (± 2 dB)	dB re 1V/Pa	-38.5
Coupler volume	mm ³	1260 @ 500 Hz
Resonance frequency	kHz	1.570
Temperature range, operation	°C / °F	-30 to 60 / -22 to 140
Temperature coefficient @250 Hz	dB/°C / dB/°F	-0.01 / -0.006
Humidity range non condensing	% RH	0 to 80
ANSI standard		S3.7
ITU-T recommendations		P.57
CE/RoHS compliant/WEEE registered		Yes/Yes/Yes
Connector type		Microdot 10/32
Weight	g / oz	0.8 / 28.219

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

Included

GRAS RA0045-S1	Prepolarized Ear Simulator According to IEC 60318-4 (60711)
GRAS 26CB	¼" CCP Preampfier
RS0010	Generic Adapter Ring
RA0119	Pistonphone Adapter

Optional

GRAS AA0070	3 m Microdot - BNC cable
-----------------------------	--------------------------

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

GRAS Worldwide

Subsidiaries and distributors in more
than 40 countries

HEAD OFFICE, DENMARK
GRAS SOUND & VIBRATION
Skovlytoften 33
2840 Holte
Denmark
Tel: +45 4566 4046
www.gras.dk
gras@gras.dk

USA
GRAS SOUND & VIBRATION
5750 S.W. Arctic Drive
Beaverton, OR 97005
Tel: 503-627-0832
Toll Free: 800-231-7350
www.gras.us
sales@gras.us

CHINA
GRAS SOUND & VIBRATION
Room 303, Building T6
Hongqiaohui, 990, Shenchang Road
Minhang District, Shanghai
China, 201106
Tel: +86 21 64203370
www.gras.com.cn
cnsales@gras.dk



ABOUT GRAS SOUND & VIBRATION

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones to industries where acoustic measuring accuracy and repeatability is of utmost importance in R&D, QA and production. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, and consumer electronics. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect and trust.

GRAS Sound
& Vibration