


# 67HA-LOWNOISE

1 m LEMO Lownoise  
Hemisphere kit



Freq range: 10 Hz to 16 kHz  
Dyn range: 6.5 dB(A) to 110 dB  
Sensitivity: 850 mV/Pa  
Measures incl. feet: Diagonal 2716 mm  
Height 1283 mm

---

The GRAS hemispheres will hold and position the measurement microphones according to the standards and have been designed with focus on your workflow; They are very easy to assemble and it is easy to position and access the DUT. Furthermore, in best GRAS tradition they are optimized acoustically for correct and repeatable measurement data.

### Introduction

The structure is made portable to achieve a high degree of freedom of location. This, combined with the easy, tool-less assembly in minutes, enables you to save expensive anechoic chamber time and to offer on-site sound power diagnostics.

The microphone positions are clearly marked to ease the mounting and maintain measurement repeatability.

The GRAS 67HA-07 1 m LEMO Lownoise Hemisphere kit, 4 channels (4 key and 4 secondary) is ISO 3746:2011 B1/ANSI S12.56 compliant and includes:

- 1x Hemisphere structure
- 4x GRAS 40HL 1/2" LEMO Lownoise Microphone Sets, cables, holders

The GRAS 67HA-08 1 m LEMO Lownoise Hemisphere kit, 10 channels (10 key and 10 secondary) is ISO 3744:2010 B2/ANSI S12.54 compliant and includes:

- 1x Hemisphere structure
- 10x GRAS 40HL 1/2" LEMO Lownoise Microphone Sets, cables, holders

The GRAS 67HA-09 1 m LEMO Lownoise Hemisphere kit, 20 channels (20 key) is ISO 3745:2012 E2/ANSI S12.55 compliant and includes:

- 1x Hemisphere structure
- 20x GRAS 40HL 1/2" LEMO Lownoise Microphone Sets, cables, holders

### Typical applications and use

Depending on the size and the emitted acoustic level of the DUT, the hemispheres will allow sound power measurements on everything from small-sized personal electrics to office machines and IT products, household appliances, power tools, and

smaller engines. The only restriction is, that the characteristic dimension of the DUT may be no more than half the measurement radius.

### Design

The hemispheres are available as preconfigured kits with 4, 10 or 20 microphone sets in 3 variations; CCP, LEMO and low-noise LEMO. In the table to the right, you will be able to find the hemisphere kit that suits your type of input module along with dynamic specifications for your application. The pre-configured hemispheres are delivered with microphone set holders that will fit all 3 microphone types. Respective cables and cable clips are included. A high-quality flight case is available.

The recommended microphone sets can be connected directly to all professional measurement systems and are as indicated available for both CCP and 7-pin LEMO inputs. If your system platform supports intelligent transducers according to IEEE 1451.4 (TEDS), the system can be set up to identify the microphone properties and position in the array.

### Calibration

All included microphone sets are delivered with individual calibration charts including sensitivity values and frequency responses. These sensitivity values can be used directly in your system setup.

For frequent measurement chain verification a reference sound source will be required. GRAS supplies 114 dB types for the standard microphone sets and a special 94 dB adapter for the low-noise sets. Depending on the use and your internal quality control requirements we recommend that the sets are re-calibrated at least every second year.

### Performance and warranty

GRAS microphone sets are made of components from our proven standard portfolio and are all

manufactured of high-quality material and branded parts that were chosen and processed to ensure life-long stability and robustness.

All parts are manufactured and assembled at the factory in Denmark by skilled and dedicated operators in a verified clean-room environment. The microphone diaphragm, body and unique protection grid are made of high-grade stainless steel and make the microphone set resistant to physical damage as well as corrosion caused by aggressive air or gasses.

This, together with the enforced gold-plated microphone terminal which guarantees a highly reliable connection, enables us to offer 5 years warranty against defective materials and workmanship. The warranty for cables is 6 months.

|  |       |          |
|--|-------|----------|
| Frequency range ( $\pm 2$ dB)  | Hz    | 10 to 16 |
| Dynamic range lower limit with GRAS preamplifier                                   | dB(A) | 6.5      |
| Dynamic range upper limit with GRAS preamplifier @ +28 V / $\pm 14$ V power supply | dB    | 110      |
| Set sensitivity @ 250 Hz ( $\pm 2$ dB)   | mV/Pa | 850      |
| IEC 61094-4 Compliance   |       | WS3P     |

## Available configurations

|              |   |
|--------------|---|
| GRAS 67HA-07 | 1 m LEMO Lownoise Hemisphere kit 4 ch.  |
| GRAS 67HA-08 | 1 m LEMO Lownoise Hemisphere kit 10 ch. |
| GRAS 67HA-09 | 1 m LEMO Lownoise Hemisphere kit 20 ch. |

## Included

|             |   |
|-------------|---|
|             | 1 m structure                                 |
| 50          | Microphone holders                            |
| GRAS 40HL   | 1/2" LEMO Lownoise Microphone Set (1 per ch.) |
| GRAS AA0009 | 10 m LEMO cable                               |

## Optional

|                           |   |
|---------------------------|---|
| GRAS RA0276               | Flight cases (2):<br>One with foam tailored for the microphones and cables<br>One with foam tailored for the structure and microphone holders |
| <a href="#">GRAS 42AP</a> | Intelligent Pistonphone (114 dB)  |
| GRAS RA0090               | Pistonphone coupler (94 dB)   |

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

# GRAS Worldwide

Subsidiaries and distributors in more  
than 40 countries

## GRAS SOUND & VIBRATION

Skovlytoften 33  
2840 Holte  
Denmark  
Tel: +45 4566 4046  
gras@gras.dk

## GRAS SOUND & VIBRATION USA

2234 East Enterprise Parkway  
Twinsburg, OH 44087  
United States  
Tel: +1 330 425 1201  
sales@gras.us

## GRAS SOUND & VIBRATION UK

Building 115  
Bedford Technology Park Thurleigh,  
MK44 2YA Bedford  
United Kingdom  
Tel: +44 1234 639552  
sales@gras.co.uk

## GRAS SOUND & VIBRATION CHINA LTD.

Rm 1606, Kodak House II  
No. 39 Healthy Street East North Point  
Hong Kong  
China  
Tel: +852 2833 9987  
sales@gras.com.cn



## About GRAS Sound & Vibration

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones to industries where acoustic measuring accuracy and repeatability is of utmost importance in R&D, QA and production. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, and consumer electronics. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect and trust.

**GRAS** Sound  
& Vibration