

GRAS 41CN

Permanent Outdoor
Microphone System for
community noise



Dyn response: 20 to 156
Sensitivity: 50 mV/Pa
90° incidence (community noise)

GRAS 41CN Permanent Outdoor Microphone System for
community noise

Typical applications and use

- Permanent outdoor-noise monitoring
- Community-noise monitoring
- IEC 60651 Type 1 noise measurements

Design

It complies with IEC 651 Type 1 and ANSI S1.41983 Type 1 requirements and can be used with any suitable electronic sound or vibration measurement system. It is PTB approved as part of an IEC 651 Type 1 system.

A 1/2-inch precision condenser microphone and thick-film preamplifier ensure maximum stability and performance. Both microphone and casing are made of stainless steel.

Precise in-situ calibration checks at 1000 Hz are enabled any time via a built-in electrostatic actuator and test oscillator.

The 41CN is fitted with anti-bird spikes, a windscreen, and a rain cap which do not impair its acoustic omnidirectional characteristics. The rain cap, which contains the electrostatic actuator, remains in position while calibrating the microphone with a pistonphone. The large dynamic range of the 41CN is obtained via a twin circuit board with a DC converter for supplying 200 V for microphone polarization as well as a 120 V supply for the preamplifier. The sensitivity of the amplifier can be adjusted by 12 dB and the gain set to -20 dB, 0 dB or +20 dB (via a pair of circuit-board jumpers) to give optimum signal-to-noise ratios on long cables. The gain is normally set to 0 dB on leaving the factory.

An A-weighting filter for increased dynamic capability is included. A circuit-board jumper is used to select either the A-weighting or linear frequency response. A-weighting or linear response can be specified when ordering, otherwise Lin-weighting will be active on delivery.

The built-in calibration oscillator can be switched on or off by short-circuiting a pin to ground in the output socket of the 41CN. The electrostatic actuator is factory set to a calibration level of 90 dBre. 20 Pa at 1000 Hz. A calibration level of 94 dB can be specified when ordering.

The electrostatic actuator and microphone assembly is electrically isolated from the casing of the 41CN; thus eliminating EMC and ground loops.

A silica-gel desiccator is located inside the lower half of the casing and a humidity-indicator window for checking the condition of a second desiccator is located in the top half.

The internal venting of the 41CN is via a capillary tube which terminates under the rain cap, it also carries the calibration-signal connection to the electrostatic actuator. By removing the rain cap (left-hand thread), the connection to the actuator is accessible.

With the windscreen removed, the unit can be readily re-calibrated using a pistonphone (fitted with Adapter RA0041); though rarely necessary since actuator calibration is normally done on a regular basis.

The Pole Adapter has a G 1 1/2-inch thread (ISO228/1). The Tripod Adapter can be screwed directly to the Pole Adapter. The output connector of the 41CN is located under the Pole Adapter and both plug and cable are well protected.

Among the available accessories is a CalibrationControl Box AC0001. This has a lead which plugs directly into the output socket of the 41CN. The AC0001 has sockets for signal output, Remote-control calibration and external power (12 -18 V DC, e.g. from a GRAS Mains/line Adapter AB0002/AB0003 *). It also has an on/off switch for local calibration control.

* AB0002 for 230 V AC; AB0003 for 120 V AC

| | | |
|--|---------------------------------------|--------------------------|
| Polarization/Connection | | 0 V / CCP |
| Dynamic range lower limit with GRAS preamplifier | dB(A) | < 20 |
| Dynamic range upper limit | dB | > 156 |
| Set sensitivity @ 250 Hz (± 2 dB) | mV/Pa | 50 |
| Output impedance | Ω | < 50 |
| Temperature range, operation | $^{\circ}\text{C} / ^{\circ}\text{F}$ | - 40 to 50 / - 40 to 122 |
| CE/RoHS compliant/WEEE registered | | Yes/Yes/Yes |
| Weight | g / oz | 1300 / 45.856 |

According to IEC 651 Type 1 and ANSI S1.4-1983 Type 1

Frequency response, 90° incidence, re. 1000Hz:

20 Hz - 80 Hz: ± 1.0 dB

80 Hz - 4 kHz: ± 0.7 dB

4 kHz - 8 kHz: ± 1.0 dB

8 kHz - 12 kHz: ± 1.5 dB

12 Hz - 20 kHz: + 1.5 dB, - 5 dB

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

Included items

| | |
|-----------------------------|---|
| GRAS AM0052 | Complete Windscreen for 41AM/CN |
| GRAS AM0038 | Multi spanner/wrench (tool for dismantling the microphone assembly) |
| GRAS AM0037 | Transport protection cap |
| GRAS AM0033 | Tripod adapter |
| GRAS AM0029 | Pole adapter |
| GRAS AE0001 | Plug |

Optional items

| | |
|--------------------------------|--|
| GRAS AC0001 | Calibration Control Box for 41AM/CN |
| GRAS AB0002 | Mains/line power supply (230 VAC/EU connector) |
| GRAS AB0006 | Mains/line power supply (230 VAC/UK connector) |
| GRAS AB0003 | Mains/line power supply (120 VAC/US connector) |
| GRAS AA0003 | 3 m LEMO 6-pin - LEMO 6-pin Cable for outdoor microphone |
| GRAS AA0002 | 10 m LEMO 6-pin - LEMO 6-pin Cable for outdoor microphone |
| GRAS AA0001 | 20 m LEMO 6-pin - LEMO 6-pin Cable for outdoor microphone |
| GRAS AA0004 | 50 m LEMO 6-pin - LEMO 6-pin Cable for outdoor microphone |
| GRAS AA0015 | 100 m LEMO 6-pin - LEMO 6-pin Cable for outdoor microphone |
| GRAS AA0016 | 200 m LEMO 6-pin - LEMO 6-pin Cable for outdoor microphone |
| GRAS AA0086-CL | Customized Length LEMO 6-pin - LEMO 6-pin Cable for outdoor microphone |
| GRAS 42AP | Intelligent Pistonphone, Class 0 |
| GRAS 42AG | Multifunction Sound Calibrator, Class 1 |
| GRAS RA0041 | Adapter for Pistonphone calibration |
| GRAS RA0087 | Special key (tool for dismantling the microphone assembly) |
| GRAS AM0009 | Windscreen for 41AM/CN (5 pcs, foam only, as spare for AM0052) |

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

GRAS Worldwide

Subsidiaries and distributors in more
than 40 countries

GRAS SOUND & VIBRATION A/S
Skovlytoften 33
2840 Holte
Denmark
Tel: +45 4566 4046
gras@gras.dk

GRAS SOUND & VIBRATION USA
2234 East Enterprise Parkway
Twinsburg, OH 44087
United States
Tel: +1 330 425 1201
sales@gras.us

GRAS SOUND & VIBRATION UK
Building 115
Bedford Technology Park Thurleigh,
MK44 2YA Bedford
United Kingdom
Tel: +44 1234 639552
sales@gras.co.uk

GRAS SOUND & VIBRATION CHINA LTD.
Rm 1606, Kodak House II
No. 39 Healthy Street East North Point
Hong Kong
China
Tel: +852 2833 9987
sales@gras.com.cn



About GRAS Sound & Vibration

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones to industries where acoustic measuring accuracy and repeatability is of utmost importance in R&D, QA and production. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, and consumer electronics. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect and trust.

GRAS Sound
& Vibration